


FTCBI Insulated Flat Braid in Coil, Tinned Copper – FTCBI15-16 (503600)



- Braids in coil are mainly used for power distribution or earthing applications
- Non-magnetic material
- Tinned finish provides a theft-deterrent appearance

EAC

Part Number	FTCBI15-16
Article Number	503600
Material	Copper Polyvinylchloride
Finish	Tinned
Nominal Current	120 A
Cross Section	31.57 kcmil
Number of Wires	896
Wire Diameter	0.006"
Length	328'
Thickness	0.14"
Width	0.7"
Unit Weight	0.4 lb
Insulation Thickness	0.04"
Insulation Voltage	450 V
Temperature	158 °F Max
Flammability Rating	UL® 94V-0
Certifications	EAC 0234251 (Russian Federation)
Standard Packaging Quantity	100 m
UPC	78285687472
EAN-13	3479775036007

Unit weight is per meter (3.28').

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2015 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.



ERICO®