


FTCBI Insulated Flat Braid in Coil, Tinned Copper – FTCBI15-25 (503610)



- Braids in coil are mainly used for power distribution or earthing applications
- Non-magnetic material
- Tinned finish provides a theft-deterrent appearance

EAC

| Part Number | FTCBI15-25 |
|-----------------------------|----------------------------------|
| Article Number | 503610 |
| Material | Copper Polyvinylchloride |
| Finish | Tinned |
| Nominal Current | 150 A |
| Cross Section | 25 mm ² |
| Number of Wires | 1,404 |
| Wire Diameter | 0.15 mm |
| Length | 100 m |
| Thickness | 3.5 mm |
| Width | 25 mm |
| Unit Weight | 0.29 kg |
| Insulation Thickness | 1 mm |
| Insulation Voltage | 450 V |
| Temperature | 70 °C Max |
| Flammability Rating | UL® 94V-0 |
| Certifications | EAC 0234251 (Russian Federation) |
| Standard Packaging Quantity | 100 m |
| UPC | 78285687473 |
| EAN-13 | 3479775036106 |

Unit weight is per meter (3.28').

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2015 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.



ERICO®