


ISO-TP Low Voltage Male/Female Insulators – ISOTP50F8M8 (542070)



- Halogen free
- High resistance to leakage current
- Great stability of electrical and mechanical parameters
- Fiberglass reinforced
- UL® Recognized in E125470 and evaluated for dielectric withstand rating of 1,500 VAC/DC
- RoHS compliant



Part Number	ISOTP50F8M8
Article Number	542070
Material	Glass Fibre Reinforced Polyamide Steel
Finish	Electrogalvanized
Working Temperature	-40 to 130 °C
Insulation Voltage	1,000 VAC 1,500 VDC
Flammability Rating	UL® 94V-0
Height (H)	50 mm
Hex Width (W)	50 mm
Depth (D)	57 mm
Diameter (Ø)	41 mm
Thread Size 1 (TS1)	M8
Thread Length (TL)	17 mm
Thread Size 2 (TS2)	M8
Thread Depth (TD)	15 mm
Static Load 1 (F1)	20,000 N
Static Load 2 (F2)	10,000 N
Unit Weight	0.15 kg
Certifications	cURus



Part Number	ISOTP50F8M8
Standard Packaging Quantity	25 pc
UPC	78285687517
EAN-13	3479775420707

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2015 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

